

## PINGHU MEISHENG ELECTROMECHANICAL EQUIPMENT SALES CO LTD

18 WENJIAO RD, ZHONGDAI INDUSTRIAL DISTRICT, PINGHE ZHEJIANG 314200 CN

**M(b)(c)(a)**

Polyamide 66 (PA66), furnished as pellets

Color	Min Thk (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str
NC, BK	0.8	V-0	4	0	-	-	-
	1.6	V-0	3	0	-	-	-
	3.2	V-0	0	0	-	-	-

Comparative Tracking Index (CTI): -

Inclined Plane Tracking (IPT): -

Dielectric Strength (kV/mm): -

Volume Resistivity (10<sup>X</sup> ohm-cm) : -

High-Voltage Arc Tracking Rate (HVTR): -

High Volt, Low Current Arc Resis (D495): -

Dimensional Stability (%): -

(a) - Denotes an alpha character a-z inclusive, representing customer's geographical location.

(b) - Denotes the numbers 00-99, exclusive of number 23, representing a customer code.

(c) - Denotes the numbers 01-44, representing 1-44% fiberglass content.

ANSI/UL 94 small-scale test data does not pertain to building materials, furnishings and related contents. ANSI/UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in the components and parts of end-product devices and appliances, where the acceptability of the combination is determined by UL.

Report Date: 2013-11-27

Last Revised: 2014-01-09

© 2014 UL LLC

**IEC and ISO Test Methods**

Test Name	Test Method	Units	Thickness Tested (mm)	Value
Flammability	IEC 60695-11-10	Class (color)	0.8	V-0 (NC, BK)
			1.6	V-0 (NC, BK)
			3.2	V-0 (NC, BK)
Glow-Wire Flammability (GWFI)	IEC 60695-2-12	C	-	-
Glow-Wire Ignition (GWIT)	IEC 60695-2-13	C	-	-
IEC Comparative Tracking Index	IEC 60112	Volts (Max)	-	-
IEC Ball Pressure	IEC 60695-10-2	C	-	-
ISO Heat Deflection (1.80 MPa)	ISO 75-2	C	-	-
ISO Tensile Strength	ISO 527-2	MPa	-	-
ISO Flexural Strength	ISO 178	MPa	-	-
ISO Tensile Impact	ISO 8256	kJ/m <sup>2</sup>	-	-
ISO Izod Impact	ISO 180	kJ/m <sup>2</sup>	-	-
ISO Charpy Impact	ISO 179-2	kJ/m <sup>2</sup>	-	-

© 2014 UL LLC